The Delphion Integrated View

Get Now: PDF More choices		Tools:	Add to Work File: Create new Wor
View: Expand Details INPADOC Jump to:	Тор	Go to: Derwent	⊠ <u>Ema</u>

PTitle: EP0848981A1: Pressure swing adsorption plant to separate oxygen fr

and process to operate the same[German][French]

PDerwent Title: Pressure swing adsorption plant for recovery of atmospheric oxygen -

comprises first vacuum pump and second pump comprising rotary blower

with pre-cooling air inlet openings [Derwent Record]

PCountry: EP European Patent Office (EPO)

FKind: A1 Publ. of Application with search report i

Finventor: Amlinger, Heinrich;

PAssignee: SGI-PROZESS-TECHNIK GmbH

News, Profiles, Stocks and More about this company

Published / Filed: 1998-06-24 / 1997-11-10

PApplication EP1997000119614

Number:

郞IPC Code: B01D 53/047; B01D 53/053;

@ECLA Code: B01D53/053; C01B13/02D4D; F04C23/00; F04C29/04;

Priority Number: 1996-12-11 <u>DE1996019651458</u> 1997-06-18 <u>DE1997019725678</u>

PAbstract: Pressure swing adsorption plant for recovery of atmospheric

oxygen@ The pressure swing adsorption plant recovers

atmospheric oxygen. The adsorbers (1, 2) contain synthetic zeolite, and are alternately connected to an air blower (3), and vacuum pumps, which carry out desorption. Two vacuum pumps (13, 14) are connected in series, forming a unit (12). The second vacuum pump (14) is a rotary blower with pre-cooling air inlet openings (33, 34) introducing a defined flow of atmospheric air. The main inlet of this pump is connected to the outlet of the first vacuum pump (13), with no intermediate cooler or water injection. Control of the vacuum

pumping unit (12) produces a desorption pressure of 300-500 mbar.

PINPADOC Show legal status actions Get Now: Family Legal Status Report Legal Status:

PDesignated AT BE CH DE DK ES FI FR GB GR IE IT LI LU MC NL PT SE

Country: Show 15 known family members

PDescription: Expand full description

+ Bezugszeichenliste



Prirst Claim: Show all claims 1. Druckwechselanlage zur Gewinnung von Sauerstoff aus der Luft, welche zumindest einen Adsorber (1, 2) mit synthetischem Zeolith hat, an welchem zum wechselnden Betrieb ein Luftgebläse (3) die Adsorptionsluft und ein Vakuumpumpstand (12 zur Desorption des Adsorbers (1, 2) angeschlossen sind, wobei der Vakuumpumpstand (12) zwei hintereinander geschaltete Vakuumpumpen (13, 14) hat, dadurch gekennzeichnet, dass in Strömungsrichtung gesehen die zweite Vakuumpumpe (14) eine voreinlassgekühlte Drehkolbenpumpe mit Kühllufteintrittsöffnungen (33, 34) zum definierten Einströmen von Außenluft atmosphärischen Drucks ist, dass der Einlassstutzen (37) der zweiten Vakuumpumpe (14) ohne Verwendung einer Gaskühlung durch Wassereinspritzung oder durch einen Wärmetauscher mit dem Auslass der ersten Vakuumpumpe (13) Verbindung hat und dass der Vakuumpumpstand (12) mit Steuereinrichtungen zum Erzeugen eines Desorptionsdruckes zwischen 300 mbar und 500 mbar versehen ist.

POther Abstract CHEMABS 129(07)083339Y CHEMABS 129(07)083340S DERABS C98-Info: 111921











this for the Gallery...

© 1997-2004 Thomson

Research Subscriptions | Privacy Policy | Terms & Conditions | Site Map | Contact Us | H